




OPTIONS & ORDERING INFORMATION

| SX3CVT | | | | | | | MHz |
|--------|------------------|-------------------|-------------------------|--------------------|--------------------|------------------|-------------------------------------|
| | Supply Voltage * | Operating Temp. * | Temperature Stability * | Tri-state Function | Package type | Pulling ** | Frequency in MHz |
| | 18 = +1.8V | C = 0° / +50°C | 0.5 = ±0.5 ppm | F = No Tri-state | 4P = 4-pad version | 05 = ±5 ppm min. | Please specify the frequency in MHz |
| | 25 = +2.5V | D = -10° / +60°C | 1.0 = ±1.0 ppm | | | | |
| | 28 = +2.8V | F = -20° / +70°C | 1.5 = ±1.5 ppm | | | | |
| | 30 = +3.0V | G = -30° / +75°C | 2.0 = ±2.0 ppm | | | | |
| | 33 = +3.3V | H = -30° / +85°C | 2.5 = ±2.5 ppm | | | | |
| | | K = -40° / +85°C | 3.0 = ±3.0 ppm | | | | |

* Note : Not all combinations are possible , please consult us.

** Other pulling range is available on customer specification

OUTLINE DIMENSIONS (MM)



Pin Connections

#1 : Control Voltage

#2 : GND

#3: Output

#4 :Vdd