


# A18ST

## CLIPPED SINE WAVE THRU-HOLE TCXO

### FEATURES

- Thru-hole package
- Wide frequency range
- Adjustable Frequency
- Applications: Base Stations, Test equipment,...

18.3 x 11.7 x 4.5 mm




Item	Specification						
Frequency Range	1.0 MHz to 125.0 MHz						
Output Logic	Clipped Sine Wave						
Supply Voltage V <sub>dd</sub> (see options)	+3.3 V ±5%		+5.0 V ±5%				
Supply Current I <sub>dd</sub>	10 mA max		15 mA max				
Frequency Tolerance	±1.0 ppm max. at 25°C ±2°C (one hour after reflow)						
Frequency Stability vs Temperature (see options)		±0.5 ppm	±1.0 ppm	±1.5 ppm	±2.0 ppm	±2.5 ppm	±3.0 ppm
	0° to +50°C	o	o	o	o	o	o
	-10° to +60°C	◇	o	o	o	o	o
	-20° to +70°C	x	o	o	o	o	o
	-30° to +75°C	x	◇	o	o	o	o
	-30° to +85°C	x	◇	◇	o	o	o
	-40° to +85°C	x	◇	◇	o	o	o
o = available		◇ = please contact us			x = not available		
Frequency Stability vs Aging	±1.0 ppm max. per year at 25°C						
Frequency Stability vs Voltage Change	±0.2 ppm max., for a ±5% input voltage change						
Frequency Stability vs Load Change	±0.2 ppm max., for a ±10% load condition change						
Output Level	≥0.8 V p-p						
Output Load	10 kΩ // 10 pF						
Start-up Time	3 ms max.						
Phase noise	Offset / dBc / Hz	10 Hz	100 Hz	1 kHz	10 kHz	100 kHz	
	(typical)						
	10.000 MHz	-95 dBc / Hz	-130 dBc / Hz	-140 dBc / Hz	-145 dBc / Hz	-150 dBc / Hz	
38.880 MHz	-85 dBc / Hz	-110 dBc / Hz	-140 dBc / Hz	-150 dBc / Hz	-150 dBc / Hz		
Mechanical Frequency Tuning (see options)	±3.0 ppm min. tuning						
Packing Unit	100 pcs / box						
<b>Customer specifications on request</b>							

## OPTIONS & ORDERING INFORMATION

A18ST	.....	.....	- .....	.....	.....	..... MHz	.....
Supply Voltage	Operating Temp. *	Temperature Stability *	Tri-state Function	Package type	Frequency in MHz	Mechanical Tuning	
33 = +3.3V	C = 0° / +50°C	0.5 = ±0.5 ppm	F = No Tri-state	4P = 4-pad version	Please specify the	-T = Trimmer option	
50 = +5.0V	D = -10° / +60°C	1.0 = ±1.0 ppm			frequency in MHz		
	F = -20° / +70°C	1.5 = ±1.5 ppm					
	G = -30° / +75°C	2.0 = ±2.0 ppm					
	H = -30° / +85°C	2.5 = ±2.5 ppm					
	K = -40° / +85°C	3.0 = ±3.0 ppm					

(\*) Note : Not all combinations are possible, please consult us.

## OUTLINE DIMENSIONS



**Pin Connections**

#1 : NC

#7 : GND

#8: Output

#14 : Vdd