


SX5CQV HCMOS SURFACE MOUNT VOLTAGE CONTROLLED CRYSTAL CLOCK OSCILLATOR

FEATURES

- SMD package
- Phase jitter less then 0.6 ps
- Tri-state function
- Applications: Optical, SONET, xDSL, SDH, ...

5.0 x 3.2 x 1.3 mm



Item	Specification	
Frequency Range	50.0 MHz ~ 245.0 MHz	
Output Logic	CMOS	
Overall Frequency Stability *	± 20 ppm ~ ± 100 ppm (see options)	
Operating Temperature Range	0 ~ +70 °C commercial application (see options) -40 ~ +85 °C industrial application (see options)	
Supply Voltage Vdd	+2.5 V ±5%	+3.3 V ±10%
Supply Voltage Center	+1.25 V	+1.65 V
Control Voltage Range	0.2 V to 2.3 V	0.3 V to 3.0 V
Supply Current Idd	40 mA max (depends of frequency)	
Output Level	VOH ≥ 0.9 Vdd	VOL ≤ 0.1 Vdd
Output Load	15 pF	
Symmetry	45 / 55 %	
Rise Time / Fall Time Fr / Ff	3.0 ns max.	
Tri-state Function	pin #2 = high or open pin #2 = low	pin #4 ==> oscillation pin #4 ==> high impedance
Start-up Time	10 ms max.	
Integrated Phase Jitter (12 kHz to 20 MHz band)	0.6 ps typical	
Phase Noise (typical)	Offset	Freq. 122.880MHz
	10 Hz	-68 dBc / Hz
	100 Hz	-99 dBc / Hz
	1 kHz	-115 dBc / Hz
	10kHz	-125 dBc / Hz
	100 kHz	-130 dBc / Hz
Frequency Pulling Range	standard ±90 ppm min. ; ±100 ppm min. ; ±150 ppm min. (see options)	
Linearity	6% typical ; 10% max.	
Slope Polarity	Positive (Increasing control voltage always increases output frequency)	
Modulation Bandwidth	10 kHz min. (-3 dB)	
Input Impedance	1MΩ typ.	
Packing Unit	1000pcs / reel	
Soldering Condition	260 °C, 10 sec x2 max	
	Customer specifications on request	

(*) Includes initial tolerance @+25°C, stability over operating temperature, stability vs. load change, stability vs. supply change and one year aging


OPTIONS & ORDERING INFORMATION

SX5CQV

Supply Voltage	Operating Temp. *	Overall Stability *	Tri-state Function	Package type	Pulling *	Frequency in MHz
25 = +2.5 V	E = 0° / +70°C	20 = ±20 ppm	E2 = Tri-state, pin #2	6P = 6-pad version	90 = ±90 ppm min.	Please specify the frequency in MHz
33 = +3.3 V	F = -20° / +70°C	25 = ±25 ppm	F = No Tri-state		100 = ±100 ppm min.	
	K = -40° / +85°C	30 = ±30 ppm 50 = ±50 ppm 100 = ±100 ppm			150 = ±150 ppm min.	

(*) Note : Not all combinations are possible, please consult us.

OUTLINE DIMENSIONS



Pin Connections	#1 : Control Voltage	#2 : E/D or NC	#3: GND
	#4 : Output	#5 : NC	#6: Vdd